

R	RADIAL COAXIAL CONNECTORS	- TECHNICAL DATA	R214.318.722
STRAIGHT HD CONNECTOR C-C MALE CRIMP CABLE 3.6/75 DOUBLE SCREEN PACK 20		Issue : 9618	Page 1 / 2
		Series : HDC 43	

Q96149Z

PLUG HDC43/5GTIS

(PERCAGE PANNEAU)

(MOUNTING HOLE)

	MM		INCH	
	maxi	mini	maxi	mini
A	7.55	7.50	0.297	0.295

CABLES : BT3002

CHARACTERISTICS	
NOMINAL IMPEDANCE	75 Ω
FREQUENCY RANGE	0-3 GHz
TEMPERATURE RATING	-40/+100 °C
VSWR	NA + 0 x F(GHz)Max1
RF INSERTION LOSS	NA $\sqrt{F}$ (GHz) dB Max1
VOLTAGE RATING	NA Vrms Max
DIELECTRIC WITHSTANDING VOLTAGE	1500 Vrms min
INSULATION RESISTANCE	5000 M Ω min
HERMETIC SEAL	NA Atm.cm3/s
LEAKAGE (pressurized only)	NA Mpa
WEIGHT	10 gr

STANDARDISATION	
	-
	-
	-
	-
CABLE RETENTION	150 N min
CENTER CONTACT RETENTION	
Axial force - mating end	22 N min
Axial force - opposite end	NA N min
Torque (Min)	NA cm.N min
RECOMMENDED TORQUES	
Mating	NA cm.N
Panel nut	NA cm.N
Clamp nut	NA cm.N

CONSTRUCTION		
CONNECTOR PARTS	MATERIALS	FINISH
BODY	BRASS	GOLD
OUTER CONTACT	-	-
CENTER CONTACT	BRASS	GOLD
INSULATOR	PTFE	-
FERRULE	BRASS	NICKEL
BROWMET	POLYACETAL	-
-	-	-
-	-	-
-	-	-

ISSUE	REVISION No	DESCRIPTION	BY	DATE
-	-	-	-	-
-	-	-	-	-
-	-	-	-	-
-	-	-	-	-

Initiated on **29/09/94**

Approval by **MARTIN**

The information given here is subject to change without notice. Design changes may be in order to improve the product.

K DE A